

# Roof Walkway Matting Advanced

External safety walkway system with four-way drainage



Watco Roof Walkway Matting Advanced takes roof safety to the next level. Taking all the best features of our original Roof Walkway Matting, with an added four-way drainage system, a redesigned top bar with a deeper cut for enhanced slip resistance and to give you peace of mind, a ten-year warranty. Even in the storm conditions, Roof Walkway Matting will provide superior performance, protecting the roof structure from damage, while the cross directional top ribs ensure safety underfoot.



## Colours



Light Grey



White



Yellow



Black\*

\*600mm only

Samples are available on request. While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

## Areas of use:

- All flat or gently sloping roofs where regular access is required

## Features:

- Deeper cut pattern
- Two-layer construction for added strength and durability
- Flexible, one-piece construction
- Quick and easy to apply – loose lay, no fixings required
- Self draining open grid design
- Weight holds matting in place
- Certified slip resistance (DIN 51130: R11; ASTM E303 Dry/Wet with lines along–lines across 78-90 / 63-71)
- Excellent four-way drainage (DIN 51130: V10)
- Contours to roof structure and protects the membrane
- Stands strong in winds up to 125mph
- Resistant to most acids, alkalines and oils.
- Available in rolls: 10m x 14mm thick and 600mm / 910mm / 1220mm wide

## Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Roof Walkway Matting Advanced**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



# Roof Walkway Matting Advanced

External safety walkway system with four-way drainage

## Specification

<b>Acoustic</b>	Excellent sound absorption.
<b>Availability</b>	Available in rolls 14mm thick: 10m x 600mm - 10m x 910mm - 10m x 1220mm.
<b>Chemical Resistance</b>	Resistant to most acids, alkalines and oils. For more information, please contact our expert advisors.
<b>Cleaning</b>	Simply lift or roll to clean. Easy to clean with a high-pressure hose.
<b>Composition</b>	Flexible Polyvinyl Chloride (PVC).
<b>Drainage</b>	DIN 51130:v10
<b>Environment</b>	Watco Roof Walkway Matting Advanced is 100% recyclable.
<b>Fire Resistance</b>	EN ISO 13501 - 1 : 2007 - CFL - S1
<b>Hygiene</b>	Made from non-porous PVC that's naturally resistant to bacteria growth.
<b>Primer Required</b>	No.
<b>Properties</b>	Two-layer construction and channelled underbars. Deep cut open grid pattern in a flexible PVC.
<b>Reversion</b>	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in a hot environment.
<b>Slip Resistance</b>	DIN 51130:R11 ASTM E303 Dry/Wet with lines along-lines across 78 - 90 / 63 - 71
<b>Suitable for</b>	Flat or gently sloping roofs.
<b>Thermal</b>	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
<b>Thickness</b>	14mm
<b>UV Light</b>	Resistant to PVC degradation.
<b>Weight</b>	5.8kg/m <sup>2</sup> (1.2 lb/sq.ft)
<b>Warranty</b>	Ten years. The product will remain functional and will not degrade in such a manner as to cause leaks in the PVC roof membrane.
<b>Wind Resistance</b>	Roof Walkway Matting Advanced remains stable in winds up to 60mph (96km/h). Tests in Florida have previously shown when laid flat on a stable platform Roof Walkway Matting Advanced remained in position for wind speeds of 125mph (200km/h).