

# Roof Walkway Matting TPO

External safety walkway system compatible with EPDM and TPO membranes




Watco Roof Walkway Matting TPO is specifically designed to protect flat roofs from heavy foot traffic, dropped tools and maintenance equipment. Made from flexible TPO, the embossed surface ensures a firm grip underfoot (Rated wet 54 PTV), providing safe access for staff and maintenance workers.

The durable two layer, open grid self-draining system provides excellent drainage and with no fixings required, Roof Walkway Matting TPO can be installed quickly and easily, even in adverse weather conditions, remaining stable in winds up to 55mph.



## Colours



Light Grey



White



Yellow

Samples are available on request. While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

## Areas of use:

- All flat or gently sloping roofs where regular access is required

## Features:

- Two-layer construction for added strength and durability
- Flexible, one-piece construction
- Quick and easy to apply – loose lay, no fixings required
- Self draining open grid design
- Weight holds matting in place
- Certified slip resistance - PTV: Dry - 67 (with lines), 97 (across lines); Wet - 54 (with lines), 77 (across lines)
- Contours to and protects EPDM and TPO roof membranes
- Stands strong in winds up to 55mph
- Available in 10m rolls, simply cut to fit on site

## Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Roof Walkway Matting TPO**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



# Roof Walkway Matting TPO

External safety walkway system compatible with TPO and EPDM membranes

## Specification

<b>Acoustic</b>	Excellent sound absorption.
<b>Availability</b>	Available in rolls 12mm thick: 10m x 600mm (33' x 2') and 10m x 750mm (33' x 2'6").
<b>Cleaning</b>	Simply lift or roll to clean. Easy to clean with a high-pressure hose.
<b>Composition</b>	Thermoplastic polyolefin
<b>Drainage</b>	DIN 51130: V10
<b>Environment</b>	Roof Walkway Matting TPO is 100% recyclable. No substances included in the SVHC list under REACH. Phthalate free.
<b>Fire Resistance</b>	EN ISO 13501-1:2007-Dfl-S1
<b>Slip Resistance</b>	ASTM E303 (PTV): Dry - 67 (with lines), 97 (across lines); Wet - 54 (with lines), 77 (across lines).
<b>Suitable for</b>	Flat or gently sloping roofs.
<b>Thermal</b>	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
<b>Thickness</b>	12mm
<b>Weight</b>	5.2kg/m <sup>2</sup> (1.1lb/sq.ft)
<b>Warranty</b>	Four years.
<b>Wind Resistance</b>	When loose laid, Roof Walkway Matting TPO can withstand winds up to 55mph. In laboratory conditions, on a flat stable platform at The University Of Hertfordshire, School of Aerospace, Automotive & Design Engineering, Roof Walkway Matting TPO remained stable in wind speeds up to 88mph.