Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

# atco<sup>®</sup> SAFETY DATA SHEET

Concrex Deep Fill Cold Set - Curing Agent

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- : Concrex Deep Fill Cold Set Curing Agent
- Product name Product description Product type UFI
- : repair product
- : Liquid.
  - : Y9P0-D0U5-Y00X-F8RJ

### **1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses		
Consumer Industrial Professional		
Uses advised against	Reason	
None identified.	-	

### 1.3 Details of the supplier of the safety data sheet

Watco UK Limited
Eastgate Court
195-205 High Street
Guildford
Surrey
GU1 3EH
Telephone no.: +44 (0) 1483 425000 (08:00 - 18:00)
Fax no.: +44 (0) 1483 428888
e-mail address of person : rpmeurohas@rustoleum.eu
responsible for this SDS

### 1.4 Emergency telephone number

### National advisory body/Poison Centre

Telephone number Ireland	: 809 2166 Available 8am to 10pm 7 days per week
<u>Supplier</u>	
Telephone number Ireland	: +353 19014670
Hours of operation	: 24/7

## **SECTION 2: Hazards identification**

2.1	Classification	of the	substance	or mixture	

Product definition : Mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT RE 1, H372 Aquatic Chronic 3, H412 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Concrex Deepfill Cold Set - Curing Agent

## **SECTION 2: Hazards identification**

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	<ul> <li>H314 - Causes severe skin burns and eye damage.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H361 - Suspected of damaging fertility or the unborn child.</li> <li>H372 - Causes damage to organs through prolonged or repeated exposure.</li> <li>H412 - Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements		
General	:	P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	:	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P280 - Wear protective gloves, protective clothing and eye or face protection.</li> <li>P260 - Do not breathe vapour.</li> </ul>
Response	:	<ul> <li>P308 + P313 - IF exposed or concerned: Get medical advice or attention.</li> <li>P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON</li> <li>CENTER or doctor. Rinse mouth. Do NOT induce vomiting.</li> <li>P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor.</li> <li>P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> </ul>
Storage		Immediately call a POISON CENTER or doctor. P405 - Store locked up.
Disposal	-	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Phenol, styrenated 2-piperazin-1-ylethylamine 2,2'-iminodiethylamine
Supplemental label elements	:	EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Supplemental label elements : Detergents - Regulation (EC) No 907/2006	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	<u>ier</u>	<u>its</u>
Containers to be fitted with child-resistant fastenings	:	Yes, applicable.
Tactile warning of danger	:	Yes, applicable.

Concrex Deepfill Cold Set - Curing Agent

## SECTION 2: Hazards identification

### 2.3 Other hazards

### Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

: None known. Other hazards which do not result in classification

### SECTION 3: Composition/information on ingredients

Mixture 3.2 Mixtures

Ire	a	n	d

	•	IVIIX

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Phenol, styrenated	REACH #: 01-2119980970-27 EC: 262-975-0 CAS: 61788-44-1	≥10 - ≤25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
2-piperazin-1-ylethylamine	REACH #: 01-2119471486-30 EC: 205-411-0 CAS: 140-31-8 Index: 205-411-0	≥10 - ≤25	Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Repr. 2, H361 STOT RE 1, H372 Aquatic Chronic 3, H412	ATE [Oral] = 1470 mg/kg ATE [Dermal] = 866 mg/kg	[1]
2,2'-iminodiethylamine	EC: 203-865-4 CAS: 111-40-0 Index: 612-058-00-X	≤5	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317	ATE [Oral] = 1080 mg/kg ATE [Dermal] = 1090 mg/kg	[1] [2]
ethanol	REACH #: Not yet registered EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≤3	Flam. Liq. 2, H225 Eye Irrit. 2, H319	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

Eye contact	:	Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	-	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/sy	<u>mptoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations

Concrex Deepfill Cold Set - Curing Agent

Concrex Deepfill Cold Set - Curing Ag	en
<b>SECTION 4: First aid</b>	l measures
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations
4.3 Indication of any immed	ate medical attention and special treatment needed
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	rom the substance or mixture
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Date of issue/Date of revision

## **SECTION 6: Accidental release measures**

### 6.3 Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)Recommendations: Not available.Industrial sector specific: Not available.solutions

Date of issue/Date of revision

Concrex Deepfill Cold Set - Curing Agent

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

### **Occupational exposure limits**

#### Ireland

Product/ingredient name	Exposure limit values
2,2'-iminodiethylamine	NAOSH (Ireland, 3/2016). Absorbed through skin. OELV-8hr: 4 mg/m <sup>3</sup> 8 hours. OELV-8hr: 1 ppm 8 hours.
ethanol	NAOSH (Ireland, 1/2020). OELV-15min: 1000 ppm 15 minutes.

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
ethanol	DNEL	Long term Oral	87 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	114 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	206 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	950 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	950 mg/m³	Workers	Systemic

### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail	
titanium dioxide	Fresh water	0,127 mg/l		
	Marine	>1 mg/l	-	
	Sewage Treatment	>100 mg/l	-	
	Plant	Ū		
	Fresh water sediment	>1000 mg/kg	-	
	Marine water sediment	>100 mg/kg	-	
	Soil	100 mg/kg	-	
	Marine water	0,0184 mg/l	-	
	Fresh water	0,184 mg/l	-	

### 8.2 Exposure controls

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Individual protection measures

Date of issue/Date of revision

## **SECTION 8: Exposure controls/personal protection**

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Recommended: chemical splash goggles and/or face shield.

### **Skin protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber (0.5mm) gloves
	The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: (EN 467) Overalls buttoned to the neck and wrist. or lab coat
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type AX) (as filter combination A-P2) (EN 141)
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

······································	
Physical state	: Liquid.
Colour	: Grey.
Odour	: Ammoniacal.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: >100°C (>212°F)
Flammability (solid, gas)	: Not available.
Lower and upper explosion limit	: Not available.
Flash point	: Closed cup: >100°C (>212°F)
Auto-ignition temperature	: Not relevant due to nature of the product.
Decomposition temperature	: Not available.
рН	: Not available.
pH : Justification	: Not available.
Viscosity	: Not available.
Solubility(ies)	- : · · · · · · · · · · · · · · · · · ·
Media	Result
cold water	Not soluble
hot water	Not soluble

ŝ,

hot water	Not soluble
Solubility in water	Not available.
Miscible with water	No.
Partition coefficient: n-octanol/ water	Not applicable.

### Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50				
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method		
2-piperazin-1-ylethylamine	0,04	0,0053						
Evaporation rate	: Not	: Not available.						
Relative density	: 1,2							
Density	: 1,20	086 g/cm³	[20°C (68°F)]					
Vapour density	: Not available.							
Explosive properties	: Not available.							
Oxidising properties	: Not available.							
Particle characteristics								
Median particle size	: Not	: Not applicable.						

Concrex Deepfill Cold Set - Curing Agent

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: No specific data.			
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

# **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Phenol, styrenated	LD50 Dermal	Rabbit	>5010 mg/kg	-
•	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	2500 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2-piperazin-1-ylethylamine	LD50 Dermal	Rabbit	880 mg/kg	-
	LD50 Dermal	Rabbit	880 uĽ/kg	-
	LD50 Dermal	Rat	866 mg/kg	-
	LD50 Oral	Rat	1470 mg/kg	-
	LD50 Oral	Rat	2140 mg/kg	-
2,2'-iminodiethylamine	LD50 Dermal	Rabbit	1090 mg/kg	-
	LD50 Oral	Rat	1080 mg/kg	-
ethanol	LC50 Inhalation Vapour	Rat	124700 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	7 g/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Phenol, styrenated	2500	N/A	N/A	N/A	N/A
2-piperazin-1-ylethylamine	1470	866	N/A	N/A	N/A
2,2'-iminodiethylamine	1080	1090	N/A	N/A	N/A
ethanol	7000	N/A	N/A	124,7	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Phenol, styrenated	Eyes - Mild irritant	Rabbit	-	0.1 Mililiters	-
	Skin - Mild irritant	Rabbit	-	0.5 Mililiters	-
2-piperazin-1-ylethylamine	Eyes - Moderate irritant	Rabbit	-	24 hours 20	-
				milligrams	
	Skin - Severe irritant	Rabbit	-	24 hours 5	-
				milligrams	
2,2'-iminodiethylamine	Skin - Moderate irritant	Rabbit	-	500	-
				milligrams	
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
ate of issue/Date of revision	: 15/03/2023 Date of previo	us issue : 13	/12/2022	Vers	on : 3.01 10/

Concrex Deepfill Cold Set - Curing	Agent				
SECTION 11: Toxic	ological information				
	Eyes - Moderate irritant	Rabbit	-	milligrams 100 microliters	-
	Eyes - Moderate irritant	Rabbit	-	0,066666667 minutes 100	-
	Eyes - Severe irritant	Rabbit	-	milligrams 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
Conclusion/Summary	·	·	·	····	
Skin	: Causes severe skin burns and eye damage.				
Eyes	: Causes serious eye damage.				
Respiratory	: May cause damage to organs through prolonged or repeated exposure if inhaled.				
Sensitisation					
Conclusion/Summary					
Skin	: May cause an allergic ski	n reaction.			
Respiratory	: Based on available data, the classification criteria are not met.				
Mutagenicity					
Conclusion/Summary	: Based on available data, the classification criteria are not met.				
<b>Carcinogenicity</b>					
	he carcinogenic hazard of this p ment of particle clearance mecl			able dust is inhaled	d in quantities
Conclusion/Summary	: Based on available data,	the classification	n criteria a	are not met.	
Reproductive toxicity					
Conclusion/Summary	: Suspected of damaging t	he unborn child.	Suspecte	ed of damaging fer	tility.
Teratogenicity					
Conclusion/Summary	: Based on available data,	the classification	n criteria a	are not met.	
Specific target organ tox	<u>city (single exposure)</u>				
Not available.					

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-piperazin-1-ylethylamine	Category 1	-	-

### **Aspiration hazard**

Not available.

Information on likely routes : Routes of entry anticipated: Dermal, Inhalation. of exposure

#### Potential acute health effects Eye contact : Causes serious eye damage.

	- , , , , , , , , , , , , , , , , , , ,
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes severe burns. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

11/18

# **SECTION 11: Toxicological information**

	-
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health eff	<u>icts</u>	
Not available.		
Conclusion/Summary	: Based on available data, the classification criteria are not met.	
General	: Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	,
Carcinogenicity	: No known significant effects or critical hazards.	
Mutagenicity	: No known significant effects or critical hazards.	
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.	

### 11.2 Information on other hazards

11.2.1 Endocrine disrupting propertiesNot available.11.2.2 Other informationNot available.

Concrex Deepfill Cold Set - Curing Agent

# **SECTION 12: Ecological information**

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-piperazin-1-ylethylamine	Acute LC50 2190000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
2,2'-iminodiethylamine	Acute EC50 345600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute IC50 16 mg/l	Daphnia spec.	48 hours
	Acute LC50 53500 µg/l Fresh water	Daphnia spec Daphnia magna	48 hours
	Acute LC50 248 mg/l	Fish	96 hours
	Acute LC50 1014000 µg/l Fresh water	Fish - Poecilia reticulata	96 hours
ethanol	Acute EC50 17,921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 5680 mg/l Fresh water	Daphnia spec Daphnia magna - Neonate	48 hours
	Acute LC50 12720 ppm Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 4,995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0,375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks

**Conclusion/Summary** : May cause long lasting harmful effects to aquatic life.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum	
ethanol	-	97,36 % - Readily - 20 days	s -	-	
-       67,74 % - Readily - 5 days       -       -         Conclusion/Summary       : This product has not been tested for biodegradation. Based on available data, the classification criteria are not motion.       -					
Product/ingredient name	classification criteria are not met.  Photolysis Biodegrad				
ethanol	-	-		Readily	

### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-piperazin-1-ylethylamine	-1,48	2.8 to 6.3	low
2,2'-iminodiethylamine	-5,58		low
ethanol	-0,35		low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Non-volatile.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

### 13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European waste catalogue (EWC)

Waste code	Waste designation	
08 04 11*	adhesive and sealant sludges containing organic solvents or other hazardous substances	

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information					
	ADR/RID	ADN	IMDG	ΙΑΤΑ	
14.1 UN number or ID number	UN2735	UN2735	UN2735	UN2735	
14.2 UN proper shipping name	Amines, liquid, corrosive, N.O.S. (2-piperazin- 1-ylethylamine)	Amines, liquid, corrosive, N.O.S. (2-piperazin- 1-ylethylamine)	Amines, liquid, corrosive, N.O.S. (2-piperazin- 1-ylethylamine)	Amines, liquid, corrosive, N.O.S. (2-piperazin- 1-ylethylamine)	
14.3 Transport hazard class(es)	8	8	8	8	
14.4 Packing group	11	11	11	11	
14.5 Environmental hazards	No.	No.	No.	No.	
Additional information	Limited quantity : ≤ 1L Tunnel code (E)		<u>Emergency</u> <u>schedules</u> : F-A, S-B <u>Remarks</u> : ≤ 1L: Limited Quantity - IMDG 3.4	Quantity limitation Passenger and Cargo Aircraft: 1 L. Packaging instructions: 851. Cargo Aircraft Only: 30 L. Packaging instructions: 855. Limited Quantities - Passenger Aircraft: 0,5 L. Packaging instructions: Y840.	

Concrex Deepfill Cold Set - Curing Agent

# **SECTION 14: Transport information**

14.6 Special precautions for	1	Transport within user's premises: always transport in closed containers that are
user		upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not available.
according to IMO	
instruments	

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)
Annex XIV - List of substances subject to authorisation
Annex XIV
None of the components are listed.
Substances of very high concern
None of the components are listed.
Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles
Other EU regulations
VOC for Ready-for-Use : Not applicable. Mixture
Industrial emissions : Not listed (integrated pollution prevention and control) - Air
Industrial emissions : Not listed (integrated pollution prevention and control) - Water
Ozone depleting substances (1005/2009/EC) Not listed.
Prior Informed Consent (PIC) (649/2012/EC) Not listed.
Persistent Organic Pollutants (850/2004/EC) Not listed.
<u>Seveso Directive</u> This product is not controlled under the Seveso Directive. <u>Ireland</u>
Biocidal products : Not applicable. regulation

Concrex Deepfill Cold Set - Curing Agent

# SECTION 15: Regulatory information

References	<ul> <li>Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001 (S.I. No. 619 of 2001)</li> </ul>
	Safety, Health and Welfare at Work (Carcinogens) Regulations 2001 (S.I. No. 78 of 2001)
	Safety, Health and Welfare at Work (General Application) Regulations 2007
	Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by
	Regulation (EU) No. 2020/878
	REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE
	COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

### **International regulations**

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

List name		Ingredient name	Status
Not listed.			
<b>CN code</b> : 3214 10 10	00		·
Inventory list			
Australia	:	All components are listed or exempted.	
Canada	:	At least one component is not listed in DSL but all such com NDSL.	ponents are listed in
China	:	Not determined.	
<b>Eurasian Economic Union</b>	:	Russian Federation inventory: Not determined.	
Japan	:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.	
New Zealand	:	All components are listed or exempted.	
Philippines	:	At least one component is not listed.	
Republic of Korea	:	All components are listed or exempted.	
Taiwan	:	All components are listed or exempted.	
Thailand	:	Not determined.	
Turkey	:	Not determined.	
United States	:	Not determined.	
Viet Nam	:	Not determined.	
5.2 Chemical safety ssessment	:	This product contains substances for which Chemical Safety required.	Assessments are s

### **SECTION 16: Other information**

Indicates information that h	as changed from previously issued vers	ion.		
Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and 1272/2008] DMEL = Derived Minimal Effect Lev DNEL = Derived No Effect Level EUH statement = CLP-specific Haza N/A = Not available PBT = Persistent, Bioaccumulative	el ard statement	gulation (EC) No	
Date of issue/Date of revision	: 15/03/2023 Date of previous issue	: 13/12/2022	Version : 3.01	16/18

Concrex Deepfill Cold Set - Curing Agent

### **SECTION 16: Other information**

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Corr. 1, H314	Expert judgment
Eye Dam. 1, H318	Expert judgment
Skin Sens. 1, H317	Expert judgment
Repr. 2, H361	Expert judgment
STOT RE 1, H372	Expert judgment
Aquatic Chronic 3, H412	Expert judgment

### Full text of abbreviated H statements

<u>Ireland</u>			
Full text of abbreviated H statements	:	H302       H         H311       T         H312       H         H314       C         H315       C         H317       M         H318       C         H319       C         H361       S         H372       C         H411       T	lighly flammable liquid and vapour. larmful if swallowed. joxic in contact with skin. larmful in contact with skin. causes severe skin burns and eye damage. causes skin irritation. May cause an allergic skin reaction. causes serious eye damage. causes serious eye damage. causes serious eye irritation. causes serious eye irritation. causes damage to organs through prolonged or repeated exposure. foxic to aquatic life with long lasting effects. larmful to aquatic life with long lasting effects.
Full text of classifications [CLP/GHS]	:	Acute Tox. 3 Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Eye Dam. 1 Eye Irrit. 2 Flam. Liq. 2 Repr. 2 Skin Corr. 1 Skin Corr. 1 Skin Corr. 1 Skin Irrit. 2 Skin Sens. 1 STOT RE 1	ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2 REPRODUCTIVE TOXICITY - Category 2 SKIN CORROSION/IRRITATION - Category 1
Date of printing	:	15/03/2023	
Date of issue/ Date of revision	;	15/03/2023	
Date of previous issue	:	13/12/2022	
Version	:	3.01	
Notice to reader			

Concrex Deepfill Cold Set - Curing Agent

## **SECTION 16: Other information**

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.