Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

Tatco SAFETY DATA SHEET

Fastcoat Anti Slip - Curing Agent

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: Fastcoat Anti Slip - Curing Agent
Product description	: Paint
Product type	: Liquid.
UFI	: SAT0-608U-D006-JA4K

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses			
Professional use Industrial use			
Uses advised again	Reason		
Consumer use	Product is not intended for consumer use.		

1.3 Details of the supplier of the safety data sheet

Watco UK Limited Eastgate Court 195-205 High Street Guildford Surrey GU1 3EH Telephone no.: +44 (0) 1483 425000 (08:00 - 18:00) Fax no.: +44 (0) 1483 428888 e-mail address of person : rpmeurohas@rustoleum.eu

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number Ireland	: 809 2166 Available 8am to 10pm 7 days per week
<u>Supplier</u>	
Telephone number Ireland	: +353 19014670
Hours of operation	: 24/7

SECTION 2: Hazards identification

2.1 (Classification	of the	substance	or mixture	
-------	----------------	--------	-----------	------------	--

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H332 Skin Sens. 1, H317

STOT SE 3, H335

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Fast Coat Anti Slip - Curing Agent SECTION 2: Hazards identification			
Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H317 - May cause an allergic skin reaction. H332 - Harmful if inhaled. H335 - May cause respiratory irritation.	
Precautionary statements			
General	:	Not applicable.	
Prevention	:	P280 - Wear protective gloves. P284 - In case of inadequate ventilation wear respiratory protection. P271 - Use only outdoors or in a well-ventilated area.	
Response	:	P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Storage	:	Not applicable.	
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.	
Hazardous ingredients	:	polyhexamethylene diisocyanate hexamethylene-di-isocyanate	
Supplemental label elements	:	EUH204 - Contains isocyanates. May produce an allergic reaction.	
Supplemental label elements : Detergents - Regulation (EC) No 907/2006	:	Not applicable.	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.	
Special packaging requirem	en	<u>ts</u>	
Containers to be fitted with child-resistant fastenings	:	Not applicable.	
Tactile warning of danger	:	Not applicable.	

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

Fast Coat Anti Slip - Curing Agent

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Ireland

Specific Conc. % **Product/ingredient name Identifiers** Classification Туре Limits, M-factors and ATEs polyhexamethylene REACH #: ≥90 Acute Tox. 4, H332 ATE [Inhalation [1] [2] diisocyanate 01-2119485796-17 Skin Sens. 1, H317 (dusts and mists)] CAS: 28182-81-2 STOT SE 3, H335 = 1,5 mg/l List #: 931-274-8 hexamethylene-di-REACH #: ≤0,1 Acute Tox, 4, H302 ATE [Oral] = 500 [1] [2] mg/kg isocyanate 01-2119457571-37 Acute Tox. 1, H330 Skin Irrit. 2, H315 ATE [Inhalation EC: 212-485-8 CAS: 822-06-0 Eye Irrit. 2, H319 (vapours)] = 0.05Index: 615-011-00-1 Resp. Sens. 1, H334 mg/l Skin Sens. 1, H317 Resp. Sens. 1, STOT SE 3, H335 H334: C ≥ 0,5% Skin Sens. 1, H317: C ≥ 0,5% See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

List numbers have no legal significance.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Fast Coat Anti Slip - Curing Agent

SECTION 4: First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed.
	The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	-	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
5.2 Special hazards arising fi	on	i the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
5.3 Advice for firefighters Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Fast Coat Anti Slip - Curing Agent

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Additional information	:	No unusual hazard if involved in a fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Date of issue/Date of revision	: 15/03/2023 Date of previous issue : 26/08/2022 Version : 4.01 5/17

Fast Coat Anti Slip - Curing Agent

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3	Spe	cific	end	use	s)	
					- /	

Recommendations : Not available.

Industrial sector specific

solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Ireland

Product/ingredient name	Exposure limit values	
polyhexamethylene diisocyanate hexamethylene-di-isocyanate	 NAOSH (Ireland, 1/2020). Skin sensitiser. OELV-8hr: 0,02 mg/m³, (as NCO) 8 hours. OELV-15min: 0,07 mg/m³, (as NCO) 15 minutes. NAOSH (Ireland, 1/2020). Skin sensitiser. OELV-8hr: 0,005 ppm, (as NCO) 8 hours. 	
procedures atmosphere or of the ventilatio protective equip the following: E the assessmen limit values and atmospheres - of exposure to (Workplace atmospheres)	contains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness n or other control measures and/or the necessity to use respiratory oment. Reference should be made to monitoring standards, such as European Standard EN 689 (Workplace atmospheres - Guidance for t of exposure by inhalation to chemical agents for comparison with a measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be	

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
polyhexamethylene diisocyanate	DNEL	Short term Inhalation	1 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0,5 mg/m³	Workers	Local
hexamethylene-di-isocyanate	DNEL	Short term Inhalation	1 mg/m³	Workers	Local
	DNEL	Long term Inhalation	0,5 mg/m³	Workers	Local
	DNEL	Long term Inhalation	0,35 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0,7 mg/m³	Workers	Local

PNECs

Fast Coat Anti Slip - Curing Agent

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Compartment Detail	Value	Method Detail
polyhexamethylene diisocyanate	Fresh water	0,127 mg/l	-
	Marine	0,0127 mg/l	-
	Fresh water sediment	266700 mg/kg dwt	-
	Marine water sediment	26670 mg/kg dwt	-
	Soil	53182 mg/kg dwt	-
	Sewage Treatment	38,28 mg/l	-
	Plant	-	
hexamethylene-di-isocyanate	Fresh water	0,127 mg/l	-
	Marine	0,0127 mg/l	-
	Sediment	266700 mg/kg dwt	-
	Soil	53182 mg/kg dwt	-
	Sewage Treatment	38,28 mg/l	-
	Plant		
	Fresh water	>0,05 mg/l	-
	Fresh water sediment	>1,33 mg/kg	-
	Marine water	>0,005 mg/l	-
	Marine water sediment	>0,133 mg/kg	-
	Sewage Treatment	55,6 mg/l	-
	Plant		
	Soil	>0,066 mg/kg	-

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): butyl rubber (0.6 mm) gloves
	estimated. > 0 hours (breakinough time). buty rubber (0.0 mm) gives

Fast Coat Anti Slip - Curing Agent

SECTION 8: Exposure controls/personal protection

		The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 141)
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

o. I mormation on basic physica	
Physical state	: Liquid.
Colour	: Clear. Colourless.
Odour	: Mild.
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not relevant due to nature of the product.
Flammability (solid, gas)	: Not available.
Lower and upper explosion limit	: Not available.
Flash point	: Closed cup: 158°C (316,4°F) [DIN 53213]
Auto-ignition temperature	: 445°C (833°F)
Decomposition temperature	: Not available.
рН	: Not applicable.
pH : Justification	: Product is non-polar/aprotic.
Viscosity	: Dynamic: 1200 mPa·s [DIN EN ISO 3219]
Solubility(ies)	:
Not available.	
Solubility in water	: Not available.
Miscible with water	: No.
Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	: <0,3 kPa (<2,2502 mm Hg)
Evaporation rate	: Not available.

Date of issue/Date of revision

: 15/03/2023 Date of previous issue

Fast Coat Anti Slip - Curing Agent

SECTION 9: Physical and chemical properties

Relative density	: 1,16
Density	: 1,13 to 1,19 g/cm ³ [20°C (68°F)] [DIN 53217]
Vapour density	: Not available.
Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity			
10.1 Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	:	The product is stable.	
10.3 Possibility of hazardous reactions	:	Hazardous reactions or instability may occur under certain conditions of storage or use. Amines and alcohols may cause exothermic reactions. Evolution of gases in closed containers causes overpressure and produces a risk of bursting. Precautions should be taken to minimise exposure to atmospheric humidity or water. CO_2 will be formed, which, in closed containers, could result in pressurisation.	
10.4 Conditions to avoid	:	No specific data.	
10.5 Incompatible materials	:	No specific data.	
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
polyhexamethylene diisocyanate	LC50 Inhalation Dusts and mists	Rat - Female	0,39 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
hexamethylene-di- isocyanate	LC50 Inhalation Dusts and mists	Rat	0,124 mg/m ³	4 hours
	LCLo Inhalation Dusts and mists	Rat	60 mg/m³	4 hours
	LD50 Dermal	Rabbit	>7000 mg/kg	-

Conclusion/Summary : Harmful if inhaled.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Fast Coat Anti Slip - Curing Agent	N/A	N/A	N/A	11	N/A
polyhexamethylene diisocyanate	N/A	N/A	N/A	N/A	1,5
hexamethylene-di-isocyanate	500	N/A	N/A	0,05	N/A

Irritation/Corrosion

Date of issue/Date of revision

Fast Coat Anti Slip - Curing Agent

SECTION 11: Toxicological information

	ogical information				
Product/ingredient name	Result	Species	Score	Exposure	Observation
polyhexamethylene diisocyanate	Eyes - Cornea opacity	Rabbit	1	-	-
	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Oedema	Rabbit	1	4 hours	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
hexamethylene-di-isocyanate	Eyes - Redness of the conjunctivae	Rabbit	3	-	-
	Skin - Erythema/Eschar	Rabbit	3	-	-

Conclusion/Summary

Skin : Based of

: Based on available data, the classification criteria are not met.

: Based on available data, the classification criteria are not met.

Eyes Respiratory

: May cause respiratory irritation.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
polyhexamethylene diisocyanate	Respiratory	Guinea pig	Not sensitizing
hexamethylene-di-	skin skin Respiratory	Guinea pig Mouse Guinea pig	Sensitising Sensitising Sensitising
isocyanate	skin	Guinea pig	Sensitising

Conclusion/Summary

: May cause an allergic skin reaction.

Respiratory

: Based on available data, the classification criteria are not met.

Mutagenicity

Skin

Product/ingredient name	Test	Experiment	Result
polyhexamethylene diisocyanate	OECD 471	Subject: Bacteria	Negative
-	OECD 476	Subject: Mammalian-Animal	Negative
hexamethylene-di-isocyanate	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 476	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 474	Experiment: In vivo Subject: Mammalian-Animal	Negative
Conclusion/Summary	: Based on available da	ta, the classification criteria are not m	et.
Carcinogenicity			
Conclusion/Summary	: Based on available da	ta, the classification criteria are not m	et.
Reproductive toxicity			
Conclusion/Summary	: Based on available da	ta, the classification criteria are not m	et.

Conclusion/Summary : Based on available data, the classification criteria are not met. <u>Specific target organ toxicity (single exposure)</u>

Teratogenicity

Fast Coat Anti Slip - Curing Agent

SECTION 11: Toxicological information

5			
Product/ingredient name	Category	Route of exposure	Target organs
Fast Coat Anti Slip - Curing Agent	Category 3	-	Respiratory tract irritation
polyhexamethylene diisocyanate	Category 3	-	Respiratory tract irritation
hexamethylene-di-isocyanate	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Not available. of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: Harmful if inhaled. May cause respiratory irritation.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

<u>Short term exposure</u>		
Potential immediate effects	: N	lot available.
Potential delayed effects	: N	lot available.
Long term exposure		
Potential immediate effects	: N	lot available.
Potential delayed effects	: N	lot available.
Defendent strande beselfte off		

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
polyhexamethylene diisocyanate	Sub-chronic LC50 Inhalation Dusts and mists	Rat	14,7 mg/m³	6 hours; 5 days per week Intermittent
	Sub-acute LC50 Inhalation Dusts and mists	Rat	89,9 mg/m³	6 hours; 5 days per week Intermittent
	Sub-acute LCLo Inhalation Dusts and mists	Rat	4,3 mg/m ³	6 hours; 5 days per week

Fast Coat Anti Slip - Curing Agent

SECTION 11: Toxicological information

	Chronic NOAEL Inhalation Dusts and mists	Rat	3,3 mg/m³	Intermittent 6 hours; 5 days per week Intermittent		
hexamethylene-di- isocyanate	Chronic LCLo Inhalation Vapour	Rat	0,025 p.p.m.	30 days; 6 hours per day Intermittent		
Conclusion/Summary	: Based on available data, th	e classification crite	eria are not met.			
General	 Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. 					
Carcinogenicity	: No known significant effect	s or critical hazards				
Mutagenicity	: No known significant effect	s or critical hazards				
Reproductive toxicity	: No known significant effect	s or critical hazards				

11.2 Information on other hazards

- 11.2.1 Endocrine disrupting properties
- Not available.
- 11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
polyhexamethylene diisocyanate	Acute EC50 >10000 mg/l	Bacteria	3 hours
,	Acute EC50 >100 mg/l	Daphnia spec.	48 hours
	Acute IC50 >1000 mg/l	Algae - Scenedesmus subspicatus	72 hours
	Acute LC50 >100 mg/l	Fish	96 hours
hexamethylene-di-isocyanate	Acute EC50 >77,4 mg/l	Algae	72 hours
	Acute EC50 842 mg/l	Bacteria	3 hours

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
polyhexamethylene diisocyanate	OECD 301C	2 % - Not readi	ly - 28 days	-	-
hexamethylene-di-isocyanate	OECD 301F	42 % - 10 days		-	-
	EU 301F Ready Biodegradability - Manometric Respirometry Test	42 % - 28 days		-	-
Conclusion/Summary	: Based on availa	able data, the cla	assification crite	eria are not m	et.
Product/ingredient name	Aquatic half-life		Photolys	is	Biodegradability
polyhexamethylene diisocyanate hexamethylene-di-isocyanate	Fresh water 0,32	days, 23°C	50%; 0.49	day(s)	Not readily Not readily

12.3 Bioaccumulative potential

Fast Coat Anti Slip - Curing Agent

SECTION 12: Ecological information

Product/ingredient name	LogPow	BCF	Potential
polyhexamethylene diisocyanate	5,54	367,7	low
hexamethylene-di-isocyanate	0,02	57,63	low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Non-volatile.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

 Methods of disposal
 The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

	Waste code	Waste designation
	08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
S	pecial precautions	: This material and its container must be disposed of in a safe way. Care should be

taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information ADR/RID **ADN** IMDG ΙΑΤΑ 14.1 UN number Not regulated. Not regulated. Not regulated. Not regulated. or ID number 14.2 UN proper shipping name Date of issue/Date of revision : 26/08/2022 : 15/03/2023 Date of previous issue Version : 4.01 13/17

Fast Coat Anti Slip - Curing Agent

SECTION 14: Transport information						
14.3 Transport hazard class(es)	-	-	-	-		
14.4 Packing group	-	-	-	-		
14.5 Environmental hazards	No.	No.	No.	No.		

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

SECTION 15: Regulatory information

: Not available.

15.1 Safety, health and enviro	onmental regul	ations/legislation spec	ific for the substand	e or mixture
EU Regulation (EC) No. 190	7/2006 (REACH	1		
Annex XIV - List of substa	nces subject to	authorisation		
Annex XIV				
None of the components a	re listed.			
Substances of very high	<u>concern</u>			
None of the components a				
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicat	le.		
Other EU regulations				
VOC	:			
VOC for Ready-for-Use Mixture	: 2004/42/EC	- IIA/j: 500g/l (2010). <	= 80g/I VOC.	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed			
Ozone depleting substanc	<u>es (1005/2009/E</u>	<u>C)</u>		
Not listed.				
Prior Informed Consent (P Not listed.	<u>IC) (649/2012/E</u>	<u>C)</u>		
Persistent Organic Polluta	<u>nts (850/2004/E</u>	<u>:C)</u>		
Date of issue/Date of revision	: 15/03/2023	Date of previous issue	: 26/08/2022	Version

Fast Coat Anti Slip - Curing Agent

SECTION 15: Regulatory information

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

<u>Ireland</u> Biocidal products regulation	: Not applicable.
References	 Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001 (S.I. No. 619 of 2001) Safety, Health and Welfare at Work (Carcinogens) Regulations 2001 (S.I. No. 78 of 2001) Safety, Health and Welfare at Work (General Application) Regulations 2007 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC

International regulations

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

List name		Ingredient name	Status
Not listed.			
CN code	: 3208 90 91 00		

Inventory list

Inventory list		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Thailand	:	All components are listed or exempted.
Turkey	:	All components are listed or exempted.
United States	:	All components are active or exempted.
Viet Nam	;	All components are listed or exempted.
15.2 Chemical safety assessment	:	This product contains substances for which Chemical Safety Assessments are still required.

Fast Coat Anti Slip - Curing Agent

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
-	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
,	On basis of test data Calculation method Calculation method

Full text of abbreviated H statements

<u>Ireland</u>		
Full text of abbreviated H statements	:	 H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H330 Fatal if inhaled. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.
Full text of classifications [CLP/GHS]	:	Acute Tox. 1ACUTE TOXICITY - Category 1Acute Tox. 4ACUTE TOXICITY - Category 4Eye Irrit. 2SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2Resp. Sens. 1RESPIRATORY SENSITISATION - Category 1Skin Irrit. 2SKIN CORROSION/IRRITATION - Category 2Skin Sens. 1SKIN SENSITISATION - Category 1STOT SE 3SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of printing	:	15/03/2023
Date of issue/ Date of revision	:	15/03/2023
Date of previous issue	:	26/08/2022
Version	:	4.01

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

16/17

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage,

Fast Coat Anti Slip - Curing Agent

SECTION 16: Other information

application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.