

Galvaprime

Preparatory wash for galvanised surfaces to improve adhesion of paints



Usually, painting galvanised metal can be problematic, because whilst galvanising prevents the metal from rusting, it also prevents the adhesion of any coating applied to the metal. Galvaprime is a single pack primer for use on galvanised or zinc surfaces prior to the application of paints, such as, Metal Paint, Safety Grip and Roofite. Galvaprime is quickly and easily applied by brush to the surface to maximise the adhesion of the following coating.

Areas of use:

- Floors
- Ramps
- Steps
- Roofs

Features:

- Quick and easy to apply by brush
- Essential for good adhesion to zinc or galvanised metal
- Neutralises and primes surfaces
- Dries quickly and can be painted the same day



Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Galvaprime**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



Galvaprime

Preparatory wash for galvanised surfaces to improve adhesion of paints

1 Surface preparation

Remove oil, grease and dirt from the surface. Also, remove excess rust.

2 Application

Apply evenly to the surface with a brush. Once dry, the treated surface will turn black, indicating that it is ready to be painted. Blackening does not occur if the surface is heavily contaminated or effected by rust. In such case, work Galvaprime vigorously into the surface. We recommend washing the blackened surface with clear water and allowing it to dry before painting with a coating such as Metal Paint, Safety Grip or Roofite.

Do not wait more than 16 hours after the application of Galvaprime to overcoat.

Do not apply Galvaprime at temperatures below 4°C.

3 Safety

Material Safety Data Sheets are available.

4 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale. The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Galvaprime

Preparatory wash for galvanised surfaces to improve adhesion of paints

Specification

Composition	Galvaprime is a mixture of water, acids, preservatives and solvent.
Properties	Neutralises and primes galvanised surfaces, rapid drying - can be over coated the same day, essential for good adhesion of coatings to zinc and galvanised metal.
Number of Components	1
Suitable for	Floors, ramps, steps and roofs.
Usage Interior/Exterior	Exterior & interior.
Application Tools	Brush.
Cleaning Tools	Rinse thoroughly with water.
Drying Time	Touch dry in approx. 2 hours at 20°C. Surface must be dry before painting. Do not exceed 16 hours before overcoating.
Pack Size	1L
Coverage	20m ² per litre.
Shelf Life	24 months in unopened container.
Storage	Protect from frost. Do not allow to freeze.
Principle Limitations	Flammable - avoid contact with skin and eyes. In case of contact with skin, wash immediately with plenty of water. Keep out of reach of children.
Please contact us regarding applications not described here.	