

# **Watco** SAFETY DATA SHEET

Powerfloat Primer - Curing Agent

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

**Product name** : Powerfloat Primer - Curing Agent

**Product description** : Paint **Product type** : Liquid.

UFI : N890-J06M-300N-UG5H

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer use Industrial use Professional use	

Uses advised against	Reason	
None identified.	-	

### 1.3 Details of the supplier of the safety data sheet

Watco UK Limited Eastgate Court 195-205 High Street Guildford Surrey

GU13EH

Telephone no.: +44 (0) 1483 425000 (08:00 - 18:00)

Fax no.: +44 (0) 1483 428888

e-mail address of person : rpmeurohas@rustoleum.eu

responsible for this SDS

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Telephone number Ireland : 809 2166

Available 8am to 10pm 7 days per week

**Supplier** 

Telephone number Ireland : +353 19014670

Hours of operation : 24/7

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

Date of issue/Date of revision 1/16 : 19/08/2022 Date of previous issue Version: 4 : No previous validation

## SECTION 2: Hazards identification

**Hazard pictograms** 

Signal word : Danger

**Hazard statements** : H318 - Causes serious eye damage.

**Precautionary statements** 

**General** : P103 - Read carefully and follow all instructions.

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

**Prevention** : P280 - Wear eye or face protection.

: P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several Response

minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

: Not applicable. **Storage** 

: P501 - Dispose of contents and container in accordance with all local, regional, **Disposal** 

national and international regulations.

**Hazardous ingredients** : Formaldehyde, polymers with 1,3-benzenedimethanamine, bisphenol A,

diethylenetriamine-glycidyl Ph ether reaction products, epichlorohydrin, propylene

oxide and triethylenetetramine, reaction products with glycidyl o-tolyl ether,

sulfamates (salts)

Supplemental label

elements

: EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed.

Do not breathe spray or mist.

Supplemental label elements : Detergents -

Regulation (EC) No

907/2006

: Not applicable.

: Not applicable.

**Annex XVII - Restrictions** on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Special packaging requirements

Containers to be fitted

with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

Date of issue/Date of revision 2/16 : 19/08/2022 Date of previous issue Version: 4 : No previous validation

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

**Ireland** 

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Formaldehyde, polymers with 1,3-benzenedimethanamine, bisphenol A, diethylenetriamine-glycidyl Ph ether reaction products, epichlorohydrin, propylene oxide and triethylenetetramine, reaction products with glycidyl o-tolyl ether, sulfamates (salts)	CAS: 238080-05-2 List #: 607-272-5	≥10 - ≤25	Acute Tox. 4, H302 Eye Dam. 1, H318  See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 511 mg/kg	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

**Type** 

[1] Substance classified with a health or environmental hazard

List numbers have no legal significance.

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**Eye contact** 

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 3/16

Powerfloat Primer - Curing Agent

## **SECTION 4: First aid measures**

### Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### **Protection of first-aiders**

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

### **Over-exposure signs/symptoms**

**Eye contact**: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

: None known.

media

### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

 Decomposition products may include the following materials: sulfur oxides

metal oxide/oxides

### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 4/16

# SECTION 5: Firefighting measures

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

**Additional information** 

No unusual hazard if involved in a fire.

### SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Do not get in eves or on skin or clothing. Do not breathe vapour or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 19/08/2022 5/16 Date of previous issue Version: 4 : No previous validation

Powerfloat Primer - Curing Agent

# **SECTION 7: Handling and storage**

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

Recommendations : Not available. : Not available.

## **Industrial sector specific** solutions

# SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

### Occupational exposure limits

**Recommended monitoring** procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

Product/ingredient name	Compartment Detail	Value	Method Detail
titanium dioxide	Fresh water	0,127 mg/l	-
	Marine	>1 mg/l	-
	Sewage Treatment	>100 mg/l	-
	Plant		
	Fresh water sediment	>1000 mg/kg	-
	Marine water sediment	>100 mg/kg	-
	Soil	100 mg/kg	-
	Marine water	0,0184 mg/l	-
	Fresh water	0,184 mg/l	-
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l	-
	Fresh water sediment	3,29 mg/kg	-
	Marine water sediment	0,329 mg/kg	-
	Soil	0,29 mg/kg	-
	Sewage Treatment	100 mg/l	-
	Plant		
propane-1,2-diol	Fresh water	260 mg/l	-
	Marine water	26 mg/l	-
	Sewage Treatment	20000 mg/l	-
	Plant		
	Fresh water sediment	572 mg/kg dwt	-
	Marine water sediment	57,2 mg/kg dwt	-

Date of issue/Date of revision 6/16 : 19/08/2022 Date of previous issue Version : 4 : No previous validation

# **SECTION 8: Exposure controls/personal protection**

				ı
	Soil	50 mg/kg dwt	-	•
1-methoxy-2-propanol	Fresh water	10 mg/l	-	
	Fresh water sediment	41,6 mg/l	-	
	Marine water sediment	4,17 mg/l	-	
	Soil	2,47 mg/l	-	
	Sewage Treatment	100 mg/l	-	
	Plant			

#### 8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead. Recommended: safety glasses with side-shields.

#### **Skin protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): butyl rubber (0.6 mm) gloves

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 7/16

Powerfloat Primer - Curing Agent

# **SECTION 8: Exposure controls/personal protection**

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour (Type A) and particulate filter (EN 141)

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

Physical state : Liquid.
Colour : Grey.
Odour : Slight

Odour threshold : Not available.

Melting point/freezing point

Initial boiling point and

boiling range

: Not relevant due to nature of the product.

Flammability (solid, gas) : Not available.

Lower and upper explosion : Not available.

limit

Flash point : Not relevant due to nature of the product.

Auto-ignition temperature : Not relevant due to nature of the product.

**Decomposition temperature**: Not available.

pH : 6 to 8 [Conc. (% w/w): 100%] [OECD 122]

**pH**: **Justification** : Not available.

Viscosity : Dynamic: 500 to 600 mPa·s [ICI Rotothinner]

: Not available.

Solubility(ies) :

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Vapour Pressure at 20°C			Var	our pressu	re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	23,8	3,2				

Evaporation rate : Not available.

Relative density : 1,48 [calculated.]

**Density** : 1,454 to 1,514 g/cm³ [20°C (68°F)] [DIN 53217]

Vapour density : Not available.

Explosive properties : Not available.

Oxidising properties : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 8/16

Powerfloat Primer - Curing Agent

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

If involved in a fire, toxic gases including CO, CO2 and smoke can be generated.

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde, polymers with 1,3-benzenedimethanamine, bisphenol A, diethylenetriamine-glycidyl Ph ether reaction products, epichlorohydrin, propylene oxide and triethylenetetramine, reaction products with glycidyl o-tolyl ether, sulfamates (salts)	LD50 Dermal	Rabbit	2500 mg/kg	-
	LD50 Oral	Rat	511 mg/kg	-

# Conclusion/Summary

: Based on available data, the classification criteria are not met.

### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Formaldehyde, polymers with 1,3-benzenedimethanamine, bisphenol A, diethylenetriamine-glycidyl Ph ether reaction products, epichlorohydrin, propylene oxide and triethylenetetramine, reaction products with glycidyl o-tolyl ether, sulfamates (salts)	511	2500	N/A	N/A	N/A

**Irritation/Corrosion** 

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 9/16

Powerfloat Primer - Curing Agent

# **SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Formaldehyde, polymers with 1,3-benzenedimethanamine, bisphenol A, diethylenetriamine-glycidyl Ph ether reaction products, epichlorohydrin, propylene oxide and triethylenetetramine, reaction products with glycidyl o-tolyl ether, sulfamates (salts)	Eyes - Visible necrosis	Rabbit	-	1 minutes 20 mg/kg	1 hours
, ,	Eyes - Visible necrosis	Rat	-	1 minutes 28 mg/kg	1 hours
	Skin - Mild irritant	Rabbit	-	-	-

#### **Conclusion/Summary**

**Skin**: Based on available data, the classification criteria are not met.

**Eyes** : Causes serious eye damage.

**Respiratory**: Based on available data, the classification criteria are not met.

**Sensitisation** 

**Conclusion/Summary** 

Skin : Based on available data, the classification criteria are not met.
 Respiratory : Based on available data, the classification criteria are not met.

### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
Formaldehyde, polymers with 1,3-benzenedimethanamine, bisphenol A, diethylenetriamine-glycidyl Ph ether reaction products, epichlorohydrin, propylene oxide and triethylenetetramine, reaction products with glycidyl o-tolyl ether, sulfamates (salts)	OECD 471	Experiment: In vitro Subject: Bacteria	Negative

### **Conclusion/Summary**

: Based on available data, the classification criteria are not met.

## **Carcinogenicity**

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

**Reproductive toxicity** 

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

**Teratogenicity** 

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 10/16

Powerfloat Primer - Curing Agent

# SECTION 11: Toxicological information

### **Aspiration hazard**

Not available.

**Information on likely routes**: Not available.

of exposure

Potential acute health effects

**Eye contact** : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Skin contact** Ingestion : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

> watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

**Potential immediate** : Not available.

effects

: Not available. Potential delayed effects

Long term exposure

**Potential immediate** : Not available.

effects

**Potential delayed effects** : Not available.

### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde, polymers with 1,3-benzenedimethanamine, bisphenol A, diethylenetriamine-glycidyl Ph ether reaction products, epichlorohydrin, propylene oxide and triethylenetetramine, reaction products with glycidyl o-tolyl ether, sulfamates (salts)	Chronic LD50 Route of exposure unreported	Rabbit	20 mg/kg	-
	Chronic LD50 Route of exposure unreported	Rat	28 mg/kg	-

**Conclusion/Summary** 

: Based on available data, the classification criteria are not met.

General No known significant effects or critical hazards.

Date of issue/Date of revision 11/16 : 19/08/2022 Date of previous issue : No previous validation Version: 4

Powerfloat Primer - Curing Agent

## **SECTION 11: Toxicological information**

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

#### 12.2 Persistence and degradability

**Conclusion/Summary**: Based on available data, the classification criteria are not met. This product has not

been tested for biodegradation.

#### 12.3 Bioaccumulative potential

Not available.

#### 12.4 Mobility in soil

Soil/water partition

: Not available.

coefficient (Koc)

Mobility : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal**: The generation of waste should be avoided or minimised wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes. European waste catalogue (EWC)

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 12/16

Powerfloat Primer - Curing Agent

# SECTION 13: Disposal considerations

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

### **Special precautions**

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market

dangerous substances, mixtures and articles

**Other EU regulations** 

and use of certain

VOC

: The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Date of issue/Date of revision : 19/08/2022 Date of previous issue 13/16 : No previous validation Version: 4

Powerfloat Primer - Curing Agent

# **SECTION 15: Regulatory information**

**VOC for Ready-for-Use** 

**Mixture** 

: IIA/j. Two-pack reactive performance coatings for specific end use such as floors.

EU limit value for this product : 140g/l (2010.) This product contains a maximum of 10 g/l VOC.

Industrial emissions (integrated pollution

prevention and control) -

: Not listed

Air

Industrial emissions (integrated pollution prevention and control) - : Not listed

. Water

Ozone depleting substances (1005/2009/EC)

Not listed.

Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

Persistent Organic Pollutants (850/2004/EC)

Not listed.

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

**Ireland** 

**Biocidal products** 

: Not applicable.

regulation References

: Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001 (S.I. No.

619 of 2001)

Safety, Health and Welfare at Work (Carcinogens) Regulations 2001 (S.I. No. 78 of

2001)

Safety, Health and Welfare at Work (General Application) Regulations 2007 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Regulation (EU) No. 2020/878

REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council

Directive 89/686/EEC

### **International regulations**

### **Stockholm Convention on Persistent Organic Pollutants**

List name	Ingredient name	Status
Not listed.		

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

List name	Ingredient name	Status
Not listed.		

**CN code** : 3209 90 00 00

**Inventory list** 

Australia : All components are listed or exempted.

Canada : At least one component is not listed.

China : All components are listed or exempted.

**Eurasian Economic Union: Russian Federation inventory:** Not determined.

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 14/16

Powerfloat Primer - Curing Agent

# **SECTION 15: Regulatory information**

Japan : Japan inventory (CSCL): At least one component is not listed.

Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : At least one component is not listed.

Republic of Korea : At least one component is not listed.

Taiwan : Not determined.
Thailand : Not determined.
Turkey : Not determined.

United States : At least one component is not listed.

Viet Nam : Not determined.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/20081

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Eye Dam. 1, H318	Expert judgment	

### Full text of abbreviated H statements

<u>Ireland</u>

Full text of abbreviated H

statements

H302 Harmful if swallowed.

H318 Causes serious eye damage.

Full text of classifications

[CLP/GHS]

Acute Tox. 4 ACUTE TOXICITY - Category 4

Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Date of printing : 15/03/2023 Date of issue/ Date of : 19/08/2022

revision

Date of previous issue : No previous validation

Version : 4

**Notice to reader** 

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this

Date of issue/Date of revision : 19/08/2022 Date of previous issue : No previous validation Version : 4 15/16

Powerfloat Primer - Curing Agent

### **SECTION 16: Other information**

safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.