

WATCO®

The UK's leading direct supplier of industrial strength flooring products

Thermoline

Preformed thermoplastic line, symbol, wording and numbering system for permanent road and warehouse marking



The Watco Thermoline system combines the longevity and excellent adhesion of thermoplastic with ease of application. It is designed for roadways, warehouses, pavements, car parks and any heavily trafficked areas.

The lines are supplied in 1m and 5m lengths for easy handling. The line, symbol, word or number is laid on the substrate and heated using the Watco Thermoline Blow Torch. The exceptionally clear, well-defined markings can be driven over within minutes.

- Suitable for internal and external use
- Lines, symbols, words and numbers are pre formed - no cutting required
- Quick application - one man operation
- Ready for use within minutes
- Tough, flexible, permanent markings

Other Watco line marking products available:




Epoxyline

A heavy duty line marking paint with excellent durability.



Trafficline

A tough acrylic paint for asphalt, tarmac and concrete.



Safety Tapes

Long lasting, self adhesive and slip resistant tapes.



Conformable Safety Tape

For application to profiled metal, ladder rungs, profiled slabs etc.

Watco Thermoline

Description

The system can be applied to most surfaces including concrete, tarmac, asphalt and metal.

The Watco Thermoline Blow Torch is powered by a standard propane gas bottle (not supplied by Watco).

Availability

Line

1m x 100mm wide - available in white or yellow, in packs of 10 and 50.

Line

5m x 100mm wide - available in white or yellow, in packs of 10.

Disabled symbol

800mm x 800mm - available in white or yellow, and in a 1.4m x 1.4 m size.



Straight arrow

2m x 100mm wide - available in white only.

Walking Man symbol

980mm - available in white or yellow.



Storage Instructions

When storing Watco Thermoline, it is essential to ensure the following:

The markings are never stood on their side or on their end. The markings must be carefully stacked and no heavy objects must be placed on top. Store at room temperature, avoiding direct sunlight. The markings must not be dropped, particularly in cold weather. If the markings are allowed to drop below room temperature, allow them to warm up before attempting to use. The markings may become brittle at low temperatures.

How to lay the markings

Position warning signs and cones if necessary and ensure all vehicles are removed from the working area. The surface of the road must be dry and clean. If there is any surface water, sweep this away and dry out dampness with a torch. If the ground is cold, heat with the blowtorch before laying the markings. This will aid adhesion to the surface of the road.

Remove the PROTECTIVE PLASTIC FILM and place into position. When laying lines, ensure they are 'butted' up correctly and straight. Set regulator at 25psi, ignite and turn torch on to required pressure. Position nozzle of blowtorch 4-6 inches above the centre of the marking at one end. With a 'pendulum' motion from side to side, bring the material to a fluid state so that the marking bubbles and then proceed down the marking using the same action. Care must be taken in the speed of the bonding. Too slow and the marking may burn, too fast and the marking may not bond. If the flame is too high and incorrectly angled, it is possible to distort the markings. Good application can be achieved with experience. If the marking is multi-layered apply base layer first and allow to cool. Then position the second layer and repeat the fixing instructions.

Allow material to cool before removing cones. If fast cooling is required, it is suggested that water may be sprayed over the markings.

Ordering

Watco Thermoline is available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

Also available
from Watco

Floor Paints & Coatings

Dustproofers & Sealers

Line Marking

Flooring

Anti Slip Coatings

Anti Slip Products

Floor Repair Materials

Screeds

Preparation Materials

Masonry Repair Materials

Wall Coatings

Exterior Products

Traffic Control

Metal Coatings

Roofing

WATCO

Watco UK Limited

Eastgate Court, 195-205 High Street, Guildford, Surrey GU1 3AW, UK
Tel: 01483 425 000 • Fax: 01483 428 888
www.watco.co.uk • E-mail: sales@watco.co.uk

Quality Certified

ISO 9001
BUREAU VERITAS
Certification



Designed, manufactured and supplied under an ISO 9001 quality management system