

# Trafficline

An easy to use marking paint for a wide variety of surfaces

Watco Trafficline is a brush applied linemarker designed for use on asphalt and tarmac surfaces (may also be used on concrete). Ideal for car parks and medium use areas.

One brush applied coat produces a flexible, hard wearing line. Suitable for interior and exterior use.



Not available in white. Yellow only



## Colours



Samples are available on request.

While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

## Areas of use:

- Car parks
- Medium trafficked areas

## Features:

- Tough, single pack, water based acrylic formulation
- High build, one coat application
- Suitable for use on most surfaces
- Excellent resistance to UV and weathering

## Need help? Speak to the experts

Our dedicated and professional team are here to help you get the best results for your project. They will talk you through the preparation and application stages when using **Trafficline**.

Call our expert team on: **01483 418 418** (Weekdays 8:00am - 5:30pm. Saturday 9:00am - 12:00pm)



# Trafficline

An easy to use marking paint for  
a wide variety of surfaces

## 1 Surface Preparation

Watco Trafficline can be applied to asphalt, tarmac, porous concrete, masonry, bricks and breeze blocks. Ensure the surface is clean, sound and dry (slightly damp is acceptable). Watco Bio-D is a solvent free degreaser which can be used on asphalt and similar surfaces. Watco Trafficline can be applied to existing paint providing all poorly bonded material is removed and glossy surfaces are sanded.

## 2 Application

Apply Watco Trafficline by brush. Avoid applying too thickly. Do not apply if rain or frost are forecast or if the temperature is below 10°C. One coat is sufficient on most surfaces. If a second coat is required, re-apply once the first coat has dried, usually around 6 hours at 20°C.

## 3 Safety

All product labels provide general safety information. Material Safety Data Sheets are available.

## 4 Ordering

Available direct from Watco UK Limited and through agents worldwide. All Watco products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Watco products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Watco.

# Trafficline

An easy to use marking paint for  
a wide variety of surfaces

## Specification

<b>Composition</b>	Water based acrylic.
<b>Number of Components</b>	1
<b>Primer Required</b>	No
<b>Number of Coats</b>	1
<b>Usage Interior/Exterior</b>	Interior & exterior.
<b>Application Tools</b>	Brush.
<b>Suitable For</b>	Asphalt, tarmac, porous concrete, masonry bricks and breeze blocks.
<b>Pack Size</b>	5L
<b>Shelf Life</b>	24 months in unopened container.
<b>Coverage</b>	100m - 200m of 50mm wide line .
<b>Curing Time</b>	Will cure sufficiently in approximately 24 hours to accept light traffic, allow 48 hours before bringing the area back into full use. Cold, damp or humid weather will delay curing.
<b>Cleaning Tools</b>	Clean applicators in warm, soapy water before the product has dried
<b>Cleaning</b>	Resistant to the normal range of industrial cleaners and most general chemicals. Strong degreasants should be tested first. Watco Floor Cleaner may be used.
<b>Storage</b>	Store in cool, dry conditions away from direct sunlight.
<b>Safety</b>	Material Safety Data Sheets are available. Food products must be removed from the area during application.
<b>Principle Limitations</b> <b>Please contact us regarding applications not described here</b>	Watco Trafficline will not bind or fill weak or defective asphalt surfaces. Do not apply in areas which will constantly be under water.