

# watco® SAFETY DATA SHEET

Bund Sealer - Resin

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Bund Sealer - Resin  
**Product description** : Coating.  
**Product type** : Liquid.  
**UFI** : Y690-10H6-T005-64KF

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Industrial uses Consumer uses Professional uses	
Uses advised against	Reason
None identified.	-

### 1.3 Details of the supplier of the safety data sheet

Watco UK Limited  
 Eastgate Court  
 195-205 High Street  
 Guildford  
 Surrey  
 GU1 3EH  
 Telephone no.: +44 (0) 1483 425000 (08:00 - 18:00)  
 Fax no.: +44 (0) 1483 428888

**e-mail address of person responsible for this SDS** : rpmeurohas@rustoleum.eu

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : +44 (0) 207 858 1228  
**Hours of operation** : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315  
 Eye Irrit. 2, H319  
 Skin Sens. 1, H317  
 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

**Ingredients of unknown toxicity** : -

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

## SECTION 2: Hazards identification

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** :

Warning

**Hazard statements** :

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

**Precautionary statements**

**General** :

P102 - Keep out of reach of children.  
P103 - Read label before use.  
P101 - If medical advice is needed, have product container or label at hand.

**Prevention** :

P280 - Wear protective gloves and eye protection:  
- butyl rubber gloves Safety glasses with side shields.

**Response** :

P302 - IF ON SKIN:  
P352 - Wash with plenty of soap and water.  
P333 - If skin irritation or rash occurs:  
P313 - Get medical attention.

**Storage** :

Not applicable.

**Disposal** :

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** :

bisphenol-A-epoxy resin, avg.mol.wght. ≤ 700; Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol; Oxirane, mono[ (C10-16-alkyloxy)methyl] derivs.; 1,4-bis(2,3-epoxypropoxy)butane

**Supplemental label elements** :

Contains epoxy constituents. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** :

Not applicable.

**Tactile warning of danger** :

Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** :

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** :

None known.

The mixture may be a skin sensitiser. It may also be a skin irritant and repeated contact may increase this effect. The mixture may be a skin sensitiser. It may also be a severe skin irritant.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

: Mixture

Product/ingredient name	Identifiers	%	Classification	
			Regulation (EC) No. 1272/2008 [CLP]	Type
Bis[4-(2,3-epoxypropoxy)phenyl]propane	EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	EC: 500-006-8 CAS: 9003-36-5	≤10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤5	Carc. 2, H351	[1] [2]
1,4-bis(2,3-epoxypropoxy)butane	REACH #: 01-2119494060-45 EC: 219-371-7 CAS: 2425-79-8 Index: 603-072-00-7	≤5	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
oxirane, mono[(C10-16-alkyloxy)methyl] derivs	EC: 268-358-2 CAS: 68081-84-5	≤5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
hydrocarbons, aromatic, C9	REACH #: 01-2119455851-35 EC: 918-668-5	≤3	Flam. Liq. 3, H226 STOT SE 3, H335 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1]
bis-[4-(2,3-epoxypropoxy)phenyl]propane	EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 2, H411	[1]
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	REACH #: 01-2119454392-40 EC: 500-006-8 CAS: 9003-36-5	≤3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
phenol, methylstyrenated	REACH #: 01-2119555274-38 EC: 270-966-8 CAS: 68512-30-1	≤1	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412	[1]
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≤1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
pine oil	EC: 616-792-1 CAS: 8002-09-3	≤0,3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

## SECTION 3: Composition/information on ingredients

### Notes

**The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ .**

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and an irritant. It contains low molecular weight epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the mixture and exposure to spray mist and vapour should be avoided.

**SECTION 4: First aid measures**

Based on the properties of epoxy constituent(s) and considering toxicological data on similar mixtures, this mixture may be a skin sensitiser and a severe irritant. It contains epoxy based reactive diluents which are moderate to severely irritating to eyes, mucous membrane and skin and are strong sensitisers. Repeated skin contact may lead to irritation and to hyper-sensitivity, possibly with cross-sensitisation to other epoxies. Single oral exposure to doses of the epoxy based reactive diluents at or close to the lethal dose has been shown to cause transient neurotoxic effects in animals in some cases. However, uptake through skin and by inhalation has not caused such effects in animals. Prolonged exposure to high concentration may cause adverse effects in target organs such as liver and kidney.

Contains bisphenol-A-epoxy resin, avg.mol.wght.  $\leq 700$ , Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol, Oxirane, mono[(C10-16-alkyloxy)methyl] derivs., 1,4-bis(2,3-epoxypropoxy)butane  
May produce an allergic reaction.

**Over-exposure signs/symptoms**

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

**4.3 Indication of any immediate medical attention and special treatment needed**

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

See toxicological information (Section 11)

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.
- Unsuitable extinguishing media** : Do not use water jet.

**5.2 Special hazards arising from the substance or mixture**

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
sulfur oxides  
halogenated compounds  
metal oxide/oxides

**5.3 Advice for firefighters**

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

## SECTION 5: Firefighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
- Additional information** : No unusual hazard if involved in a fire.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

- : Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.  
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.  
Put on appropriate personal protective equipment (see Section 8).  
Never use pressure to empty. Container is not a pressure vessel.  
Always keep in containers made from the same material as the original one.  
Comply with the health and safety at work laws.  
Do not allow to enter drains or watercourses.  
**Information on fire and explosion protection**  
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

**SECTION 7: Handling and storage****7.2 Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations.

**Notes on joint storage**

Keep away from: oxidising agents, strong alkalis, strong acids.

**Additional information on storage conditions**

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

**Seveso Directive - Reporting thresholds (in tonnes)****Danger criteria**

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

**7.3 Specific end use(s)**

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

**SECTION 8: Exposure controls/personal protection**

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters****Occupational exposure limits**

Product/ingredient name	Exposure limit values
titanium dioxide	<b>EH40/2005 WELs (United Kingdom (UK), 8/2018).</b> TWA: 10 mg/m <sup>3</sup> 8 hours. Form: inhalable dust TWA: 4 mg/m <sup>3</sup> 8 hours. Form: respirable dust

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

Product/ingredient name	Type	Exposure	Value	Population	Effects
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	DNEL	Short term Dermal	83 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Dermal	104,15 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	29,39 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	62,5 mg/kg bw/day	General population [Consumers]	Systemic

## SECTION 8: Exposure controls/personal protection

titanium dioxide	DNEL	Long term Inhalation	8,7 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Long term Oral	6,25 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Inhalation	10 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Oral	700 mg/kg bw/day	General population [Consumers]	Systemic
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	DNEL	Short term Dermal	83 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Dermal	104,15 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	29,39 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	62,5 mg/kg bw/day	General population [Consumers]	Systemic
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	DNEL	Long term Inhalation	8,7 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Long term Oral	6,25 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Dermal	17 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Dermal	68 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Short term Inhalation	29 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	9,8 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	3,9 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	13,8 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	1,7 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Inhalation	0,98 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Dermal	10 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Inhalation	7,6 mg/m <sup>3</sup>	General population [Consumers]	Systemic
	DNEL	Short term Oral	1219 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Short term Dermal	40 mg/cm <sup>2</sup>	General population [Consumers]	Local
DNEL	Short term Inhalation	2,9 mg/m <sup>3</sup>	General population [Consumers]	Local	
DNEL	Long term Dermal	2,35 mg/kg bw/day	General population [Consumers]	Systemic	
DNEL	Long term Inhalation	4,1 mg/m <sup>3</sup>	General population [Consumers]	Systemic	



## SECTION 8: Exposure controls/personal protection

	DNEL	Long term Oral	1 mg/kg bw/day	General population [Consumers]	Systemic
	DNEL	Long term Dermal	1 mg/cm <sup>2</sup>	General population [Consumers]	Local
	DNEL	Long term Inhalation	1,46 mg/m <sup>3</sup>	General population [Consumers]	Local

### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Fresh water	0,003 mg/l	-
	Marine water	0,0003 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	0,294 mg/kg dwt	-
	Marine water sediment	0,0294 mg/kg dwt	-
titanium dioxide	Soil	0,237 mg/kg dwt	-
	Fresh water	0,127 mg/l	-
	Marine	>1 mg/l	-
	Sewage Treatment Plant	>100 mg/l	-
	Fresh water sediment	>1000 mg/kg	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Marine water sediment	>100 mg/kg	-
	Soil	100 mg/kg	-
	Fresh water	0,003 mg/l	-
	Marine water	0,0003 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Fresh water sediment	0,294 mg/kg dwt	-
	Marine water sediment	0,0294 mg/kg dwt	-
	Soil	0,237 mg/kg dwt	-
	Fresh water	0,0072 mg/l	-
	Marine	0,00072 mg/l	-
	Sewage Treatment Plant	10 mg/l	-
	Fresh water sediment	66,77 mg/kg dwt	-
	Marine water sediment	6,677 mg/kg dwt	-
	Soil	80,12 mg/kg dwt	-

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## SECTION 8: Exposure controls/personal protection

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

#### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: > 8 hours (breakthrough time): Butyl rubber gloves.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

EN 374

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (as filter combination A-P2) (EN 141)

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	: Liquid.
<b>Colour</b>	: Not available.
<b>Odour</b>	: Slight
<b>Odour threshold</b>	: Not available.
<b>pH</b>	: Not available.
<b>Melting point/freezing point</b>	: Not available.
<b>Initial boiling point and boiling range</b>	: Not available.
<b>Flash point</b>	: Closed cup: >100°C

**SECTION 9: Physical and chemical properties**

<b>Evaporation rate</b>	: Not available.
<b>Flammability (solid, gas)</b>	: Non-flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
<b>Upper/lower flammability or explosive limits</b>	: Not available.
<b>Vapour pressure</b>	: Not available.
<b>Vapour density</b>	: Not available.
<b>Relative density</b>	: 1,71 to 1,72
<b>Solubility(ies)</b>	: Insoluble in the following materials: cold water and hot water.
<b>Partition coefficient: n-octanol/ water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not available.
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Not available.
<b>Explosive properties</b>	: Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
<b>Oxidising properties</b>	: Not available.

**9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see Section 7).
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO <sub>2</sub> and smoke can be generated.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Bis[4-(2,3-epoxy propoxy) phenyl] propane titanium dioxide	LD50 Dermal	Rabbit	20 g/kg	-
	LC50 Inhalation Dusts and mists	Rat	>6,82 mg/l	4 hours
	LD50 Dermal	Rabbit	>10 g/kg	-
	LD50 Oral	Rat	>24 g/kg	-
1,4-bis(2,3-epoxypropoxy) butane	LD50 Dermal	Rabbit	1130 mg/kg	-

## SECTION 11: Toxicological information

oxirane, mono[(C10-16-alkyloxy)methyl] derivs	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	1134 mg/kg	-
	LD50 Oral	Rat	1410 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
hydrocarbons, aromatic, C9 bis-[4-(2,3-epoxypropoxy)phenyl]propane	LD50 Oral	Rat	8400 mg/kg	-
	LD50 Dermal	Rabbit	20 g/kg	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	LD50 Oral	Rat	>5000 mg/kg	-
phenol, methylstyrenated	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>3600 mg/kg	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LC50 Inhalation Dusts and mists	Rat	>150 mg/m <sup>3</sup>	7 hours
pine oil	LD50 Oral	Rat	17100 mg/kg	-
	LD50 Dermal	Rabbit	5 g/kg	-
	LD50 Oral	Rat	2,1 g/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Acute toxicity estimates

Not available.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bis[4-(2,3-epoxy propoxy)phenyl] propane	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Skin - Mild irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Erythema/Eschar	Rabbit	0,7	4 hours	72 hours
1,4-bis(2,3-epoxypropoxy)butane	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 10 milligrams	-
hydrocarbons, aromatic, C9	Eyes - Mild irritant	Rabbit	-	24 hours 100 UI	-
bis-[4-(2,3-epoxypropoxy)phenyl]propane	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Skin - Mild irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Skin - Primary dermal irritation index (PDII)	Rabbit	4,1	24 hours	-
	Skin - Primary dermal irritation index (PDII)	Rabbit	5,75	24 hours	-
	Eyes - Mild irritant	Rabbit	-	-	-
pine oil	Skin - Severe irritant	Rabbit	-	24 hours 500 milligrams	-

**SECTION 11: Toxicological information****Conclusion/Summary**

- Skin** : Causes skin irritation.
- Eyes** : Causes serious eye irritation.
- Respiratory** : Based on available data, the classification criteria are not met.

**Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
Bis[4-(2,3-epoxy propoxy) phenyl] propane	skin	Mouse	Sensitising
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	skin	Guinea pig	Sensitising
	skin	Guinea pig	Sensitising
1,4-bis(2,3-epoxypropoxy) butane	skin	Guinea pig	Sensitising
bis-[4-(2,3-epoxypropoxy) phenyl]propane	skin	Mouse	Sensitising
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	skin	Guinea pig	Sensitising
	skin	Guinea pig	Sensitising
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	skin	Guinea pig	Sensitising

**Conclusion/Summary**

- Skin** : May cause an allergic skin reaction.
- Respiratory** : Based on available data, the classification criteria are not met.

**Mutagenicity**

Product/ingredient name	Test	Experiment	Result
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	OECD 476	Experiment: In vitro Subject: Mammalian-Animal	Positive
	OECD 471 OECD 474 OECD 476	Subject: Bacteria Subject: Mammalian-Animal Experiment: In vitro Subject: Mammalian-Animal	Positive Negative Positive
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	OECD 471 OECD 474 OECD 471	Subject: Bacteria Subject: Mammalian-Animal Subject: Bacteria Metabolic activation: with and without S9 metabolic activation	Positive Negative Positive
	OECD 476 OECD 474 OECD 475	Experiment: In vitro Subject: Mammalian-Animal Experiment: In vivo Subject: Mammalian-Animal Experiment: In vivo Subject: Mammalian-Animal	Negative Negative Negative

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Carcinogenicity**

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Reproductive toxicity**

## SECTION 11: Toxicological information

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol hydrocarbons, aromatic, C9	Negative	-	-	Rat	Oral: 540 mg/kg	-
	-	-	Negative	Mammal - species unspecified	Route of exposure unreported	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Negative	-	-	Rat	Oral: 540 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Bis[4-(2,3-epoxy propoxy) phenyl] propane	Positive - Dermal	Rabbit	300 mg/kg	1 days per week
	Positive - Oral	Rat	180 mg/kg	1 days per week
	Positive - Oral	Rabbit	180 mg/kg	1 days per week
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Positive - Dermal	Rabbit	300 mg/kg	6 hours; 7 days per week
	Positive - Dermal	Rabbit	100 mg/kg	6 hours; 7 days per week
	Negative - Route of exposure unreported	Rabbit - Female	>300 mg/kg	-
bis-[4-(2,3-epoxipropoxy) phenyl]propane	Positive - Dermal	Rabbit	300 mg/kg	1 days per week
	Positive - Oral	Rat	180 mg/kg	1 days per week
	Positive - Oral	Rabbit	180 mg/kg	1 days per week
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Negative - Route of exposure unreported	Rabbit - Female	>300 mg/kg	-
	Negative - Route of exposure unreported	Rat - Female	>200 mg/kg	-
	Negative - Route of exposure unreported	Rat - Female	>200 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
hydrocarbons, aromatic, C9	Category 3	-	Respiratory tract irritation
	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Product/ingredient name	Result
hydrocarbons, aromatic, C9 pine oil	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**SECTION 11: Toxicological information**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

**Long term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

**Potential chronic health effects**

Not available.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**Other information** : Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Acute EC50 1,8 mg/l	Algae	72 hours	
	Acute EC50 2 mg/l	Daphnia spec.	24 hours	
	Acute EC50 1,6 mg/l	Daphnia spec.	48 hours	
	Acute IC50 >100 mg/l	Bacteria	3 hours	
	Acute LC50 0,55 mg/l	Fish	96 hours	
	Acute LC50 2 mg/l	Fish	96 hours	
	Chronic NOEC 0,3 mg/l	Daphnia spec.	21 days	
	titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
		Acute LC50 6,5 mg/l Fresh water	Daphnia spec. - Daphnia pulex - Neonate	48 hours
	1,4-bis(2,3-epoxypropoxy) butane	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Acute EC50 75 mg/l		Daphnia spec. - Daphnia magna	24 hours	
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Acute LC50 24 mg/l	Fish - Brachydanio rerio	96 hours	
	Chronic NOEC 80 mg/l	Algae	72 hours	
	Acute EC50 1,8 mg/l	Algae	72 hours	
	Acute EC50 2 mg/l	Daphnia spec.	24 hours	
	Acute EC50 1,6 mg/l	Daphnia spec.	48 hours	
	Acute IC50 >100 mg/l	Bacteria	3 hours	

## SECTION 12: Ecological information

Oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	Acute LC50 0,55 mg/l Acute LC50 2 mg/l Chronic NOEC 0,3 mg/l Acute EC50 >100 mg/l	Fish Fish Daphnia spec. Bacteria	96 hours 96 hours 21 days 3 hours
	Acute EC50 7,2 mg/l Acute IC50 844 mg/l Acute LC50 5000 mg/l Acute LC50 1800 mg/l Acute EC50 24,5 ppm Fresh water Acute LC50 18,35 ppm Fresh water	Daphnia spec. Algae Fish Fish Daphnia spec. - Daphnia magna Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	48 hours 72 hours 96 hours 96 hours 48 hours 96 hours
pine oil			

**Conclusion/Summary** : Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Bis[4-(2,3-epoxy propoxy) phenyl] propane Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	OECD 301B	6 to 12 % - Not readily - 28 days	-	-
	OECD 301B	16 % - Not readily - 28 days	-	-
bis-[4-(2,3-epoxipropoxi) phenyl]propane Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	-	0 % - Not readily - 28 days	-	-
	OECD 301B	6 to 12 % - Not readily - 28 days	-	-
Oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	-	0 % - Not readily - 28 days	-	-
	OECD 301F	57 to 65 % - Inherent - 7 days	-	-
	OECD 301D	35 % - Not readily - 28 days	-	-

**Conclusion/Summary** : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Bis[4-(2,3-epoxy propoxy) phenyl] propane	-	-	Not readily
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	-	-	Not readily
titanium dioxide	-	-	Not readily
hydrocarbons, aromatic, C9	-	-	Readily
bis-[4-(2,3-epoxipropoxi) phenyl]propane	-	-	Not readily
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	-	-	Not readily
Oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	-	-	Not readily

### 12.3 Bioaccumulative potential



**SECTION 12: Ecological information**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Bis[4-(2,3-epoxy propoxy) phenyl] propane	3,84	3 to 31	low
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2,7	150	low
1,4-bis(2,3-epoxypropoxy) butane	-0,269	-	low
oxirane, mono[ (C10-16-alkyloxy)methyl] derivs	>3	-	low
hydrocarbons, aromatic, C9	3.7 to 4.5	10 to 2500	high
bis-[4-(2,3-epoxipropoxy) phenyl]propane	3,84	-	low
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	2,7	-	low
phenol, methylstyrenated	3,627	-	low
Oxirane, mono[ (C12-14-alkyloxy)methyl] derivs.	3,77	160 to 263	low

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Non-volatile.

**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**European waste catalogue (EWC)**

The European Waste Catalogue classification of this product, when disposed of as waste, is:

## SECTION 13: Disposal considerations

Waste code	Waste designation
20 01 27*	paint, inks, adhesives and resins containing hazardous substances





### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of split material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	UN3082	UN3082	UN3082	UN3082
<b>14.2 UN proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s. [bisphenol-A-epoxy resin, avg.mol.wght. ≤ 700]	Environmentally hazardous substance, liquid, n.o.s. [bisphenol-A-epoxy resin, avg.mol.wght. ≤ 700]	Environmentally hazardous substance, liquid, n.o.s. Marine pollutant [bisphenol-A-epoxy resin avg.mol.wght. ≤ 700]	Environmentally hazardous substance, liquid, n.o.s. [bisphenol-A-epoxy resin avg.mol.wght. ≤ 700]
<b>14.3 Transport hazard class(es)</b>	9 	9 	9 	9 
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	Yes.	Yes.	Yes.	Yes.
<b>Additional information</b>	<b>Remarks:</b> (≤ 5L: ) Exempted  ADR Tunnel code: (E)	-	<b>Emergency schedules (EmS):</b> F-A + S-F  <b>Marine pollutant (P)</b>  <b>Remarks:</b> (≤ 5L: ) Exempted	<b>Passenger and Cargo Aircraft</b> Quantity limitation: 450 L Packaging instructions: 964 <b>Cargo Aircraft Only</b> Quantity limitation: 450 L Packaging instructions: 964 <b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 30 Kg Packaging instructions: Y 964

## SECTION 14: Transport information

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**VOC** : -

**VOC for Ready-for-Use Mixture** : Not applicable.

**Europe inventory** : All components are listed or exempted.

**Black List Chemicals (76/464/EEC)** :

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
titanium dioxide	Not supported	Not supported	Not supported	Not supported

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

###### Category

E2

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**References** : EH40/2005 Workplace exposure limits  
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2016/918

#### International regulations

##### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

## SECTION 15: Regulatory information

### Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**CN code** : 3210 00 90

### International lists

#### National inventory

<b>Australia</b>	: All components are listed or exempted.
<b>Canada</b>	: Not determined.
<b>China</b>	: All components are listed or exempted.
<b>Japan</b>	: <b>Japan inventory (ENCS)</b> : Not determined. <b>Japan inventory (ISHL)</b> : Not determined.
<b>Malaysia</b>	: Not determined
<b>New Zealand</b>	: All components are listed or exempted.
<b>Philippines</b>	: Not determined.
<b>Republic of Korea</b>	: Not determined.
<b>Taiwan</b>	: All components are listed or exempted.
<b>Turkey</b>	: Not determined.
<b>United States</b>	: Not determined.
<b>Thailand</b>	: Not determined.
<b>Viet Nam</b>	: Not determined.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate
: CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
: DMEL = Derived Minimal Effect Level
: DNEL = Derived No Effect Level
: EUH statement = CLP-specific Hazard statement
: PBT = Persistent, Bioaccumulative and Toxic
: PNEC = Predicted No Effect Concentration
: RRN = REACH Registration Number
: vPvB = Very Persistent and Very Bioaccumulative

**Contains TiO2** : Yes

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Expert judgment
Eye Irrit. 2, H319	Expert judgment
Skin Sens. 1, H317	Expert judgment
Aquatic Chronic 2, H411	Expert judgment

### Full text of H-phrases referred to in sections 2 and 3

**SECTION 16: Other information**

<b>Full text of abbreviated H statements</b>	: H226 H302 H304 H312 H315 H317 H319 H332 H335 H336 H351 H411 H412 EUH066	Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.
<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 4 Aquatic Chronic 2  Aquatic Chronic 3  Asp. Tox. 1 Carc. 2 Eye Irrit. 2 Flam. Liq. 3 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A STOT SE 3	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2  LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  ASPIRATION HAZARD - Category 1 CARCINOGENICITY - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
<b>Date of printing</b>	: 17/07/2020	
<b>Date of issue/ Date of revision</b>	: 15/07/2020	
<b>Date of previous issue</b>	: 7/10/2019	
<b>Version</b>	: 2.02	
<b><u>Notice to reader</u></b>		

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.