

BITU-MEND®

An easy to use material for repairing pot-holes



AREAS OF USE

- Ideal for pot-holes in roadways, vehicle parks, loading docks, paths, airfields etc.
- On bituminous and concrete surfaces

FEATURES

- Compacts to a dense hard surface that will resist vehicle and pedestrian traffic.
- Repairs can be driven over immediately
- Extremely simple to use
- Withstands heavy traffic
- Includes easy to use primer
- Suitable for holes between 10mm and 75mm deep

DESCRIPTION

Rapid repair for pot-holed asphalt and concrete.

Watco Bitu-Mend® is a durable bitumen-based patch repair for use on exterior pot-holed asphalt and concrete. Repairs with Watco Bitu-Mend® are ready for instant trafficking.

Watco Bitu-Mend® is applied as a soft, flexible material which gradually hardens over time following application. The repair can be instantly trafficked by cars. For very heavy traffic areas or areas where forklift trucks are used, please use Bitu-Mend® Advanced.

SPECIFICATION

Composition	Polished aggregate together with liquid binder based on bitumen plus resins and adhesives.
Number of Components	2 including primer.
Colour	Black.
Usage Interior/ Exterior	Exterior only.
Application Tools	Hand shovel, tamper.
Suitable For	Concrete, sand & cement, asphalt.
Pack Size	25kg
Coverage	Approximately 0.5m ² at 25mm thick. Watco Bitu-Mend® can be applied at up to 75mm thick.

Curing	The repair may be driven over immediately and the product will harden over time following application.
Shelf Life	24 months in unopened containers.
Storage	Re-fit container lid tightly after use. Store in a warm location. Do not allow to freeze.
Safety.	All product labels provide general safety information. Material Safety Data Sheets are available. Food products must be removed from the area during application and cure.

COLOUR



Samples are available on request.
While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

PREPARATION & APPLICATION

SURFACE PREPARATION

Remove all loose material and surface water, oil etc.

APPLICATION

Pour the primer onto the prepared surface and spread using a brush. Tip or shovel out sufficient material into the hole to slightly overfill it and then compact with the back of a shovel or tamper.

In exceptional temperature conditions advice should be obtained from Watco's Technical Department.

SAFETY

Material Safety Data Sheets are available.



WATCO.CO.UK